



# Alouette Ware Wash Chemicals Inc.

Cost Effective Cleaning Solutions for Restaurants & Bars



## KLE-175 GT Upright

- Straight-Through or Corner Configuration
- Microprocessor Based Electronic Control With 72, 90, 120 or 360 Second Wash Cycles
- Built-in Chemical Metering Pumps – Detergent, Sanitizer, Rinse
- Automatic Start/Stop
- Convenient Drain/Fill Switch
- Active Wash Cycle LED Light
- Water Connection Point for Water Driven Dispensin
- Systems such as Sink Mate and Sink Bowl
- 14 Gauge #304 Stainless Steel Construction
- Front or Side Accessible Scrap Trap
- Open Impeller with Pause Cycle
- Internal Pump Screen
- Electronic Dispenser Power Terminal



### KLE-175 GT

Operating Cycle:	<b>72 Sec.</b>	<b>90 Sec.</b>	<b>120 Sec.</b>
Operating Capacity: Racks Per Hour	46	37	30
Wash Time:	37 Sec.	45 Sec.	55 Sec.
Rinse Time:	24 Sec.	30 Sec.	50 Sec.
Drain Time:	11 Sec.	15 Sec.	15 Sec.
Wash Tank Capacity:	1.75 Gallons		
Wash Pump Capacity:	57 GPM		
Recommended Wash Temperature:	140 Degrees		
Water Inlet:	3/4"		
Drain I.P.S.:	1.5"		
Wash Pump Motor:	1 HP		
Dimensions:	25.5" D x 25.5" W x 67" H		
Table Height:	34"		
Max. Clearance For Dishes:	17"		
Standard Dish Rack:	20" x 20"		
Shipping Weight:	280 Pounds		
Electrical Rating:	120V 60Hz, 240V 50/60Hz		
Load Amps:	14, 7		

