



Alouette Ware Wash Chemicals Inc.

Cost Effective Cleaning Solutions for Restaurants & Bars

KLE-235D Double Rack by

KNIGHT

A unit of **INX** Corporation



- Straight-Through, Double-Rack, Fill and Dump Operation
- Mechanical Timer Control w/ 90 sec. Wash Cycle
- 74 Racks Per Hour
- Built-in Chemical Metering Pumps - Det., Sani., Rinse
- Two 1-Horse Power Motor with Open Impeller Provide Better Cleaning Action and Reduce Pump Service
- Automatic Start/Stop
- 14 Gauge #304 Stainless Steel Pan Construction
- Internal Scrap Trap
- Top Mounted Temperature Gauge

KLE-235 D – P/N 9000023-01

Operating Capacity:	74 Racks Per Hour
Operating Cycle:	90 Seconds
Wash Time:	47 Seconds
Rinse Time:	28 Seconds
Drain:	15
Wash Tank Capacity:	3.8 Gallons
Wash Pump Capacity:	98 Gal./Min.
Recommended Wash Temperature:	120° minimum
Water Inlet:	3/4"
Drain I.P.S.	1-1/2"
Wash Pump Motor:	1HP
Dimensions:	25"x44"x67"
Table Height:	34"
Max. Clearance For Dishes:	16-3/4"
Standard Dish Rack:	(2) 20"x20"
Shipping Weight:	350 lbs.
Electrical Rating:	115V
Load Amps:	28

